HL7 FHIR 入門

HL7技術委員会
平井　正明
2019年7月19日

http://www.hl7.org/fhir/?ref=learnmore

http://www.fhir.org

何故FHIRなのか、FHIRとは何か

- 米国民全員が自身の医療情報にアクセスできる
  - ブッシュHealth IT Initiative、オバマHITECH(Meaningful Use)
  - 自身の健康管理に参加、重複処方、処方ミスの把握

なぜリソース？

- ONCの方針
  - WEBサービス (Service Oriented Architecture)
    SOA → REST→ RESTful・ROA

- HL7 V2・V3では多くの専門家が必要
  - 多くの人、多くの企業が参加できなければならない

RFH

HL7 International ← HL5

何故FHIRなのか、FHIRとは何か

- 米国民全員が自身の医療情報にアクセスできる
  - ブッシュHealth IT Initiative、オバマHITECH(Meaningful Use)
  - 自身の健康管理に参加、重複処方、処方ミスの把握
- SOA(ROA)によるWEBサービス (スマホの普及)
  - SOAP(複雑、難解だが)→REST(ROA)=RFH(FHIR)
  - 多くの人、多くの(中小も)企業が開発に参加できる
  - ほとんどの国民が医療データにアクセスできる
- そして、*重要な情報はCDA で→C-CDA*
- さらに、米国 Standard Strategy
  - 今はUS Realm ➔ World Wide へ

Blue Button Download My Data

WEB標準の復習：httpメッセージ

普段から我々が使用している環境

http://www.hl7.org/fhir

GET /www.hl7.org/fhir HTTP/1.1

```
10 6f 3f dc 59 c7 28 f0  76 45 dd d4 08 00 45 00   .o?.Y.(. vE....E.
01 12 00 00 40 00 40 06  66 0b c0 a8 0b 06 40 09   ....@.@. f.....@.
c8 23 cc b2 00 50 a5 ed  45 6b 0c 34 54 5b 80 18   .#...P.. Ek.4T[..
08 04 04 21 00 00 01 01  08 0a 1f 46 a5 47 00 00   ...!.... ...F.G..
00 00 47 45 54 20 2f 66  68 69 72 20 48 54 54 50   ..GET /f hir HTTP
2f 31 2e 31 0d 0a 63 61  63 68 65 2d 63 6f 6e 74   /1.1..ca che-cont
72 6f 6c 3a 20 6e 6f 2d  63 61 63 68 65 0d 0a 50   rol: no- cache..P
6f 73 74 6d 61 6e 2d 54  6f 6b 65 6e 3a 20 35 64   ostman-T oken: 5d
39 37 62 38 32 34 2d 61  64 64 64 2d 34 34 31 35   97b824-a ddd-4415
2d 38 35 34 38 2d 66 38  61 39 36 31 63 62 65 38   -8548-f8 a961cbe8
62 32 0d 0a 55 73 65 72  2d 41 67 65 6e 74 3a 20   b2..User -Agent:
50 6f 73 74 6d 61 6e 52  75 6e 74 69 6d 65 2f 37   PostmanR untime/7
2e 36 2e 30 0d 0a 41 63  63 65 70 74 3a 20 2a 2f   .6.0..Ac cept: */
2a 0d 0a 48 6f 73 74 3a  20 77 77 77 2e 68 6c 37   *..Host:  www.hl7
2e 6f 72 67 0d 0a 61 63  63 65 70 74 2d 65 6e 63   .org..ac cept-enc
6f 64 69 6e 67 3a 20 67  7a 69 70 2c 20 64 65 66   oding: g zip, def
6c 61 74 65 0d 0a 43 6f  6e 6e 65 63 74 69 6f 6e   late..Co nnection
3a 20 6b 65 65 70 2d 61  6c 69 76 65 0d 0a 0d 0a   : keep-a live....
```

```
0000  48 54 54 50 2f 31 2e 31  20 32 30 30 20 4f 4b 0d   HTTP/1.1  200 OK.
0010  0a 43 6f 6e 74 65 6e 74  2d 4c 65 6e 67 74 68 3a   .Content -Length:
0020  20 31 38 38 37 37 0d 0a  43 6f 6e 74 65 6e 74 2d    18877.. Content-
0030  54 79 70 65 3a 20 74 65  78 74 2f 68 74 6d 6c 0d   Type: te xt/html.
0040  0a 43 6f 6e 74 65 6e 74  2d 4c 6f 63 61 74 69 6f   .Content -Locatio
0050  6e 3a 20 68 74 74 70 3a  2f 2f 77 77 77 2e 68 6c   n: http: //www.hl
0060  37 2e 6f 72 67 2f 66 68  69 72 2f 69 6e 64 65 78   7.org/fh ir/index
```

```
0140  30 31 39 20 30 36 3a 30  36 3a 34 39 20 47 4d 54   019 06:0 6:49 GMT
0150  0d 0a 0d 0a ef bb bf 3c  21 44 4f 43 54 59 50 45   ....... < !DOCTYPE
0160  20 48 54 4d 4c 3e 0d 0a  3c 68 74 6d 6c 20 78 6d    HTML>.. <html xm
0170  6c 6e 73 3d 22 68 74 74  70 3a 2f 2f 77 77 77 2e   lns="htt p://www.
0180  77 33 2e 6f 72 67 2f 31  39 39 39 2f 78 68 74 6d   w3.org/1 999/xhtm
0190  6c 22 20 78 6d 6c 3a 6c  61 6e 67 3d 22 65 6e 22   l" xml:l ang="en"
01a0  20 6c 61 6e 67 3d 22 65  6e 22 3e 0d 0a 3c 68 65    lang="e n">..<he
01b0  61 64 3e 0d 0a 20 20 3c  74 69 74 6c 65 3e 49 6e   ad>..  < title>In
01c0  64 65 78 20 2d 20 46 48  49 52 20 76 34 2e 30 2e   dex - FH IR v4.0.
```

```
<!DOCTYPE HTML>
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" lang="en">
  <head>
    <title>Index - FHIR v4.0.0</title>
    <meta name="viewport" content="width=device-width, initial-
scale=1.0"/>
    <meta name="author" content="http://hl7.org/fhir"/>
    <link rel="stylesheet" href="fhir.css"/>
    <link rel="Prev" href="http://hl7.org/fhir/index.html"/>
```

HL5

FHIR(ROA)のリソース

全てのリソースは一意なアドレスで識別される

Resource type

http://server.org/fhir/Patient/1234

endpoint

Resource id

FHIRリソースは

- データ交換の小さな論理的に独立したユニット
- 振る舞いと意味が定義されている
- 身元と所在が明確
- トランザクションの最小単位
- 医療に関連すること

FHIRのコンセプト

- 情報をリソースとして定義する
- 80%ルール(8割ルール)
  - 標準・規格の全てが常に使用されるわけではない
  - 国、地域ごとに言語、医療・保険制度、ルール、コード体系等は同じではない（異なる）
  - そのためのExtensionの仕組み、ルールを明確にする
- Narrativeエレメントは必須
  - XHTMLで記述する
  - Narrative部は必ず処理（表示）できること

XML復習

```
<?xml version="1.0" encoding="UTF-8" ?>
<!-- XML宣言が必要 (XML文章の先頭にコメントは書けない)-->
<person>
    <name ID="00001">
      東京太郎
    </name>
    <sex>
      男
    </sex>
    <age/>
    <address>
      東京都港区虎ノ門1丁目19番9号
    </address>
</ person >
```



JSON(JavaScript Object Notation) RFC8259

- { … } の中にダブルクォーテーション “”で囲み名前と値をコロン:で区切り記述する
  {“name”:”Hirai”}
- コンマ,で区切り複数の名前:値を連結記述できる
  {“name”:”Hirai”,”Sex”:”male”
- 階層構造を持ったオブジェクトとして記述できる
  {“user”:{“name”:”Hirai”,”sex”:”male”}}
- 配列として[…]として記述できる
  {“color”:[“red”,”green”,”blue”]}
- 文字列(“ABC”),数値(123,12.3,1.23e4),ヌル値(null),真偽値(true,false),エスケープシーケンス(¥n)が使用できる
- UTF-8(BOM無し)で記述する

```
{
 "user" : {
  "name" : "Hirai",
  "age" : 69,
  "organisation" : [
   "HL7",
   "Nihon Kohden",
   "JAHIS"
    ]
  }
}
```

"{¥"resourceType¥":¥"Patient¥",¥"identifier¥":[{¥"system¥":¥"http://acme.org/MRNs¥",¥"value¥":¥"7000135¥"}],¥"name¥":[{¥"family¥":[¥"Simpson¥"],¥"given¥":[¥"Homer¥",¥"J¥"]}]}”;

Health Level Seven Internation
Index - FHIR v4.0.0
保護されていない通信
www.hl7.org/fhir/?ref=learnmore
http://www.hl7.org/fhir/?ref=learnmore
FHIR®©
FHIR R4
Home
Getting Started
Documentation
Resources
Profiles
Extensions
Operations
Terminologies
仕様書
リソース
プロファイル
This is the Current officially released version of FHIR, which is R4.
For a full list of available versions, see the Directory of published versions.
FHIRリリース版選択
0 Welcome to FHIR®
FHIR is a standard for health care data exchange, published by HL7®.
First time here?
See the executive summary, the developer's introduction, clinical introduction, or architect's introduction, and then the FHIR overview / roadmap & Timelines. See also the open license (and don't miss the full Table of Contents and the Community Credits or you can search this specification).
概要とサマリー
Level 1 Basic framework on which the specification is built
Foundation
Base Documentation, XML, JSON, Data Types, Extensions
Level 2 Supporting implementation and binding to external specifications
Implementer Support
Downloads, Version Mgmt, Use Cases, Testing
Security & Privacy
Security, Consent, Provenance, AuditEvent
Conformance
StructureDefinition, CapabilityStatement, ImplementationGuide, Profiling
Terminology
CodeSystem, ValueSet, ConceptMap, Terminology Svc
Exchange
REST API + Search
Documents
Messaging
Services
Databases
仕様カテゴリー
5つのレベル
Level 3 Linking to real world concepts in the healthcare system
Administration
Patient, Practitioner, CareTeam, Device, Organization, Location, Healthcare Service
Level 4 Record-keeping and Data Exchange for the healthcare process
Clinical
Diagnostics
Medications
Workflow
Financial

仕様カテゴリー

Level 1 Basic framework on which the specification is built
Foundation
仕様作成時の基本フレームワーク
ON, Data Types, Extensions
Level 2 Supporting implementation and binding to external specifications
Implementer Support
Downloads
実装者支援
Security & Privacy
Security
Privacy
Conformance
StructureDefinition
実装ガイドの定義
適合性テスト法
Terminology
CodeSystem
用語と関連
成果物
Exchange
Rest API、Document、メッセージ交換、データベース等の規定
Level 3 Linking to real world concepts in the healthcare system
Administration
患者、医療従事者、組織、機器、物質などを管理、トレースするための基本規定
Level 4 Record-keeping and Data Exchange for the healthcare process
Clinical
プロブレム、アレルギー、治療過程（治療計画、紹介）等臨床情報
Diagnostics
所見、各種報告書、指示等
Genomics, Specimen, ImagingStudy, etc.
Medications
処方、調剤、投薬管理、予防接種等の管理とトレース
Workflow
ケアプロセス、治療行為の技術的成果物の管理
Financial
会計、保険請求の支援
Request & Response, ExplanationOfBenefit, etc.
Level 5 Providing the ability to reason about the healthcare process
Clinical Reasoning
意思決定支援、品質管理支援
Measure/MeasureReport, etc.

規格の成熟度


安全ではありません — hl7.org
Health Level Seven International - Homepage | HL7 International
Resourcelist - FHIR v4.0.0
HL7 FHIR FHIR R4
HL7 International
Home
Getting Started
Documentation
Resources
Profiles
Extensions
Operations
Terminologies
Table of Contents > Resources
This is the current officially released version of FHIR, which is R4 (v4.0.0). For a full list of all versions, see the Directory of published versions.
1.2 Resource Index
FHIR Infrastructure Work Group
Maturity Level: N/A
Standards Status: Informative
This page is provided to help find resources quickly. There is also a more detailed classification, ontology, and description. For background to the layout on the layers in this page, see the Architect's Overview. See also the abstract Base Resources Resource and DomainResource.
Categorized
Alphabetical
R2 Layout
By Maturity
Security Category
By Standards Status
By Committee
Foundation
Conformance
CapabilityStatement N
StructureDefinition N
ImplementationGuide 1
SearchParameter 3
MessageDefinition 1
OperationDefinition N
CompartmentDefinition 1
StructureMap 2
GraphDefinition 1
ExampleScenario 0
Terminology
CodeSystem N
ValueSet N
ConceptMap 3
NamingSystem 1
TerminologyCapabilities 0
Security
Provenance 3
AuditEvent 3
Consent 2
Documents
Composition 2
DocumentManifest 2
DocumentReference 3
CatalogEntry 0
Other
Basic 1
Binary N
Bundle N
Linkage 0
MessageHeader 4
OperationOutcome N
Parameters N
Subscription 3
Base
Individuals
Patient N
Practitioner 3
PractitionerRole 2
RelatedPerson 2
Person 2
Group 1
Entities #1
Organization 3
OrganizationAffiliation 0
HealthcareService 2
Endpoint 2
Location 3
Entities #2
Substance 2
BiologicallyDerivedProduct 0
Device 0
DeviceMetric 1
Workflow
Task 2
Appointment 3
AppointmentResponse 3
Schedule 3
Slot 3
VerificationResult 0
Management
Encounter 2
EpisodeOfCare 2
Flag 1
List 1
Library 2
Summary
Diagnostics
Medications
Care Provision
Request & Response

成熟度レベル

Level 0:[Draft]現時点でビルドしたものを発行

Level 1:ビルドプロセスでwarningが無い。担当WGレベルで実質的に実装の準備ができていると認めている

Level 2:その項目が、現実的なデータとシナリオに基づいたリソースついて、独立して開発された3システム間でテスト、データ交換ができた結果をFMG(FHIR Management Group)が受け付けたもの

Level 3:その項目がTrial Use Quality Guidelinesの会議において審議され、公式な投票の対象になっていること。3組織から10実装されていること

Level 4:その項目が公式な資料として発行され、全体がテストされていること。担当WGが実質的に安定しているとに合意されていること

Level 5:その項目が2つの公式なFMM(FHIR Maturity Model)を満たしていること。1つ以上の少なくとも5つの独立した製品で実装されていること

Level 6:[Normative]その項目が現時点で安定していると考えられること



FHIRの4つのParadigm



FHIRのService Paradigm



ServiceにはRestfulインターフェース、メッセージ、ドキュメント交換などFHIRリソース組み合わせを行うことであらためてサービスを定義する必要はない



FHIRの4パラダイムの一つ：REST

(REpresentational State Transfer)



RESTとはリソースに基づいた設計基準で、RESTによるWEBサービスを行うアーキテクチュアROAをRESTfulという

リソース仕様


FHIR R4
Home
Getting Started
Documentation
Resources
Profiles
Extensions
Operations
Terminologies
Table of Contents > Resources
リソース
1.2 Resource Index
FHIR Infrastructure Work Group
Maturity Level: N/A
Standards Status: Informative
This page is provided to help find resources quickly
background to the layout on the layers in this page, see the Architect's Overview. See also the abstract Base Resources Resource and DomainResource.
ABC順
Categorized
Alphabetical
R2 Layout
By Maturity
Security Category
By Standards Status
By Committee
Foundation
Conformance
CapabilityStatement N
StructureDefinition N
ImplementationGuide 1
SearchParameter 3
MessageDefinition 1
OperationDefinition N
CompartmentDefinition 1
StructureMap 2
GraphDefinition 1
ExampleScenario 0
Terminology
CodeSystem N
ValueSet N
ConceptMap 3
NamingSystem 1
TerminologyCapabilities 0
Security
Provenance 3
AuditEvent 3
Consent 2
Documents
Composition 2
DocumentManifest 2
DocumentReference 3
CatalogEntry 0
Other
Basic 1
Binary N
Bundle N
Linkage 0
MessageHeader 4
OperationOutcome N
Parameters N
Subscription 3

FHIRリソース【例】Patient

1.2 Resource Index

FHIR Infrastructure Work Group	Maturity Level: N/A	Standards Status: Informative

This page is provided to help find resources quickly. There is also a more detailed classification, ontology, and description. For background to the layout on the layers in this page, see the Architect's Overview. See also the abstract Base Resources Resource and DomainResource.

Categorized | Alphabetical | R2 Layout | By Maturity | Security Category | By Standards Status | By Committee

Foundation

Conformance	Terminology	Security	Documents	Other
• CapabilityStatement N	• CodeSystem N	• Provenance 3	• Composition 2	• Basic 1
• StructureDefinition N	• ValueSet N	• AuditEvent 3	• DocumentManifest 2	• Binary N
• ImplementationGuide 1	• ConceptMap 3	• Consent 2	• DocumentReference 3	• Bundle N
• SearchParameter 3	• NamingSystem 1		• CatalogEntry 0	• Linkage 0
• MessageDefinition 1	• TerminologyCapabilities 0			• MessageHeader 4
• OperationDefinition N				• OperationOutcome N
• CompartmentDefinition 1				• Parameters N
• StructureMap 2				• Subscription 3
• GraphDefinition 1				
• ExampleScenario 0				

ase

Individuals	Entities #1	Entities #2	Workflow	Management
• Patient N	• Organization 3	• Substance 2	• Task 2	• Encounter 2
• Practitioner 3	• OrganizationAffiliation 0	• BiologicallyDerivedProduct 0	• Appointment 3	• EpisodeOfCare 2
• PractitionerRole 2	• HealthcareService 2	• Device 0	• AppointmentResponse 3	• Flag 1

Patientリソース

Patientリソース仕様書の構造



TYPE Icon

	リソース基本エレメント(リソース参照)
	同一のリソースの一部またはプロファイルで定義された複数エレメントを有するエレメント
	複数の異なったタイプの一つを持つことができるエレメント(下記参照)
	属性/プロパティ値を有するエレメントを記述するデータタイプのエレメント。これらはプリィミティブタイプで小文字で始まる
	その他のエレメントを記述するデータタイプのエレメント。これらはコンプレックスタイプで大文字で始まる
	他のリソースを参照するエレメント(referenceを参照)
	本エレメントは本リソースまたはプロファイ内でその他のエレメントと同一の内容を有する
	スライスのセットの導入(Slicing参照)
	コンプレックス拡張-ネストされた拡張の一つ(拡張性参照)
	値を有する拡張でネストされていない(拡張性参照)
	コンプレックス修飾拡張-ネストされた拡張の一つ(拡張性参照)
	値を有する拡張でネストされていない(拡張性参照)
	論理プロファイルのルート

キーフラッグの記号の意味

?! : ブール値を持つ修飾子

S : サポートしなければならない要素

Σ : 集合の一部の要素

I : 制約を定義するか制約の影響を受ける要素

NE: 拡張できない要素(一部のinfrastructural要素のみ)

TU :トライアル時のみ使用

N : Normative要素

D : ドラフト時の要素



Patientリソース仕様書の構造



リソース定義(例: Patient Resource)



プロファイル

- 実装ガイドや適合性リソースで適用プロセスを記述するもの
- Document, Message、Extensionを定義するもの
- 特殊な相互運用性の規定、国家規格、ケアの種類、ビジネスパターン、診療ガイドライン・詳細モデル等の定義

例
- 動的に構成が変わるシステムの振る舞いの規定
- データ入力、表示ガイド
- 医療支援(腫瘍学の紹介、アレルギー・過敏症、ケアプラン等)
- 複数のプロファイルを同時に適用
- 異なったデーアセットに対する異なったコーディングの適応
- すべての必要なエレメントの集める
- プロファイルの最大出現数を制約無くする場合
- 宣言を支援するプロファイル
- その他

Profile(構造定義)



Composition



Composition(Document) Slicing

Structure

Name	Flags	Card.	Type	Description & Constraints
Composition	TU		DomainResource	A set of resources composed into a single Elements defined in Ancestors: id, meta, i
identifier	Σ	0..1	Identifier	Version-independent identifier for the Com
period	Σ	0..1	Period	The period covered by the documentation
detail	Σ	0..*	Reference(Any)	The event(s) being documented
section	I	0..*	BackboneElement	Composition is broken into sections *+ Rule: A section must contain at least one* *+ Rule: A section can only have an emptyR*
title		0..1	string	Label for section (e.g. for ToC)
code		0..1	CodeableConcept	Classification of section (recommended) Document Section Codes (Example)
author		0..*	Reference(Practitioner | PractitionerRole | Device | Patient | RelatedPerson |	Who and/or what authored the section



Slicingによる血圧の規定

スライシング

Structure定義に従い、血圧のようにそれぞれが意味を持つサブリストとして分割させて記述するよう規定する



REST(REpresentational State Transfer)



FHIRのRESTful API

Instance Level Interactions

- **Read** : リソースの現在の状態の読み込む
  - GET [base]/Patient/100
- **Update** : id指定の既存のリソースの更新。但しなければリソースを作成する
  - PUT [base]/Patient/100
- **Delete** : リソースを削除する
  - DELETE [base]/Patient/100
- **History** : 特定のリソースの変更履歴を参照する
  - GET [base]/Patient/100/_history
- **Vread** : リソースの特定バージョンの状態の読み込む
  - GET [base]/Patient/100/_history/{vid}
- **Patch** : 既存のリソースの位置指定した所を書き換える
  - PATCH [base]/[type]/[id] {?_format=[mime-type]}

Type Level Interactions

- **Create** : サーバが特定したidで新しいリソースを作成する
  - POST [base]/Patient
- **Search** : いくつかののフィルター基準でリソースを検索する
  - GET [base]/Observation?code=3141-9
- **History** : 特定のリソースタイプの変更履歴を参照する
  - GET [base]/Patient/_history

Whole System Interactions

- **Capabilities** : システムの機能宣言を取得する(mode: full, normative, terminology)
  - GET [base]/metadata{?mode=[mode]} {&_format=[mime-type]}
- **Batch/Transaction** : 単一のインターラクションでリソースのセットを更新、作成、削除する
  - POST [base] {?_format=[mime-type]}History
- **History** : 全てのリソースの変更履歴を参照する
  - GET [base]/_history{?[parameters]&_format=[mime-type]}
- **Search** : いくつかののフィルター基準に基づいた全てのリソースタイプにまたがって検索する
  - GET [base]/Patient?name=eve

統一インターフェースには完全に適合していない

HTTPメソッド	操作
GET	リソースの取得
PUT	リソースの更新
POST	リソースの作成
DELETE	リソースの削除
HEAD	*リソースのメタデータの取得*
OPTIONS	*リソースがサポートするメソッドを調べる*

RESTful API

read	/[type]/[id]	GET	N/A	N/A	N/A	O: ETag, If-Modified-Since, If-None-Match
vread	/[type]/[id]/_history/[vid]	GET	N/A	N/A	N/A	N/A
update	/[type]/[id]	PUT	R	Resource	O	O: If-Match
patch	/[type]/[id]	PATCH	R (may be a patch type)	Patch	O	O: If-Match
delete	/[type]/[id]	DELETE	N/A	N/A	N/A	N/A
create	/[type]	POST	R	Resource	O	O: If-None-Exist
search	/[type]?	GET	N/A	N/A	N/A	N/A
	/[type]/_search?	POST	application/x-www-form-urlencoded	form data	N/A	N/A
search-all	?	GET	N/A	N/A	N/A	N/A
capabilities	/metadata	GET	N/A	N/A	N/A	N/A
transaction	/	POST	R	Bundle	O	N/A
history	/[type]/[id]/_history	GET	N/A	N/A	N/A	N/A
history-type	/[type]/_history	GET	N/A	N/A	N/A	N/A
history-all	/_history	GET	N/A	N/A	N/A	N/A
(operation)	/$[name], /[type]/$[name] or /[type]/[id]/$[name]	POST	R	Parameters	N/A	N/A
		GET	N/A	N/A	N/A	N/A
		POST	application/x-www-form-urlencoded	form data	N/A	N/A

FHIRのMessage Paradigm



メッセージはバンドル リソース



Message




```
<Bundle>
  <type value=”message"/>
  <entry>
      <MessageHeader/>
  </entry>
  <entry>
      <Observation/>
  </entry>
  <entry>
      <Patient/>
  </entry>
  <entry>
      <Device/>
  </entry>
</Bundle>
```

MessageHeaderによりSimpleなメッセージングとして使えるが、多くは
Bundleリソースによるプロファイリングにより構成される

FHIRの Document Paradigm



Documents（文書）はバンドル リソースで構成



Documents（文書）



Documents




```
<Bundle>
    <type value="document"/>
    <entry>
        <Composition/>
    </entry>
    <entry>
        <Observation/>
    </entry>
    <entry>
        <List/>
    </entry>
    <entry>
        <Condition/>
    </entry>
</Bundle>
```

リソース DEMO

HAPI Java開発Tutorialより

- サンプルプログラム
  https://github.com/FirelyTeam/fhirstarters

- RESTクライアント(Postman)
  https://github.com/FirelyTeam/fhirstarters/tree/master/postman/crud

- FHIR Hapiサーバ
  http://hapi.fhir.org/baseDstu3/Patient
  Header name → Key: Content-Type
  Header value → Value: application/fhir+json

- JAVAクラス仕様 (R4 注:1月末STU3)
  http://hapifhir.io/apidocs-dstu3/index.html

FHIRツール


安全ではありません — hl7.org
Health Level Seven International - Homepage | HL7 International
Downloads - FHIR v4.0.0
Home
Getting Started
Welcome to FH
FHIR is a standard for health care data
Level 1 Basic framework on which th
Foundation
Level 2 Supporting implementation ar
Implementer Support
Downloads,
Version Mgmt,
Use Cases,
Testing
Level 3 Linking to real world concept
Administration
Level 4 Record-keeping and Data Exc
Clinical
Allergy, Problem,
Procedure,
ShEx Schemas - ShEx definitions for validating RDF resources
Definitions - the formal definitions that define the predicates and classes used in the RDF format (not up to date)
FHIR Specification
The whole specification so that you can host your own local copy (does not include the downloads)
Implementation Tools
Validator
The official FHIR validator - a Java jar file that can be used to validate resources. See Validation Tools for further information, or Using the FHIR Validator for parameter documentation
IG Publisher
The Implementation Guide Publishing Tool (see IG Publishing documentation)
NPM Package
The NPM Package used by many of the FHIR tools (particularly the IG publisher and the validator). This contains all the conformance & example resources, and various publishing support files. Note that the tools usually find this package directly, and there's no need to download it
Translation File
Translations of common FHIR names and messages into multiple languages (see chat.fhir.org translations stream for guidance on how to add to more)
Icon Pack
The FHIR Icon at various resolutions. Any FHIR Implementation created by an organization that has attended a connectathon is allowed to use the FHIR icon in association with the application (this policy will be reviewed in the future).
Test Cases
A Collection of Test Cases. These are XML or JSON files that provide test cases for the various FHIR reference implementations to ensure correct functioning
Code Generation Support
ValueSet expansions for the value sets used in schema generation (XML or JSON) + a list of all choice elements & backbone elements. Note that names relevant for code generation, including resource names, element & slice names, codes, etc. may collide with reserved words in the relevant target language, and code generators will need to handle this
Reference Implementations
Java
HAPI-FHIR: Object Models, Parsers, Client + Server Framework, FHIR Validator, & Utilities. The specification is built with this Java code
C#
HL7.FHIR: Object models, Parsers/Serializers, Utilities, and a Client. Source code on GitHub at http://github.com/ewoutkramer/fhir-net-api
Pascal
FhirServer: Object models, Parsers/Serializers, Validator, Utilities, Client, and the FHIR Reference server. Requires Delphi (Unicode versions)
XML
XML Tools: Document Rendering Stylesheet, supplementary implementation schemas and transforms
Javascript
See the HL7 wiki for Javascript libraries (Clients and Utilities for both servers and clients)
Swift
Swift-FHIR: Object Model, Client and Utilities
Implementation Note: These reference implementations are provided for implementer interest and assistance. While they may be used (and are) in production systems, HL7 and their various contributors accept no liability for their use. Note that these reference implementations are provided to assist to implementers to adopt the specification, and some are maintained by the FHIR project team, but are not part of the specification, and implementations are not required to conform to these, nor are they subject to the formal standards process.
Full blown open source implementations for FHIR, some of which use these reference implementations, are listed on HL7 Confluence.
It is not necessary to use these particular implementations in order to be conformant. Any other approach may be used, including code generated from the schemas.
©© HL7.org 2011+. FHIR Release 4 (v4.0.0) generated on Thu, Dec 27, 2018. QA Page
Links: Search | Version History | Table of Contents | Credits | Compare to R3 | PUBLIC DOMAIN | Propose a change

Hapiツール


安全ではありません — hapifhir.io
Health Level Seven International - Homepage | HL7 International
HAPI FHIR - The Open Source FHIR API for Java
HAPI FHIR
Support
Download
GitHub Project
Documentation
Get Help
Test Server
<Hapi/>
HAPI-FHIR
fhir made simple.
FHIR
This is the homepage for the HAPI-FHIR library. We are developing an open-source implementation of the FHIR specification in Java. FHIR (Fast Healthcare Interoperability Resources) is a specification for exchanging healthcare data in a modern and developer friendly way.
Note that this is the home for the FHIR version of HAPI. If you are looking for HL7 v2 support, click here.
Watch 138
Star 778
Fork 683
build failing
coverage 76%
maven central 3.7.0
license apache 2.0
Demonstration/Test Page
A public test server is now operating at http://hapi.fhir.org. This server is built entirely using components of HAPI-FHIR and demonstrates all of its capabilities. This server is also entirely open source. You can host your own copy by following instructions on our JPA Server documentation.
Commercial Support
Commercial support for HAPI FHIR is available through Smile CDR.
Announcements
Feb 6, 2019 - HAPI FHIR 3.7.0 (Gale) Released - The next release of HAPI has now been uploaded to the Maven repos and GitHub's releases section.
This release includes support for the now-completed FHIR R4 release (FHIR 4.0.0). It also brings support for Java 11, along with a big number of bugfixes and new features.
As always, see the changelog for a full list of changes.

Patient ←→PID

Name	Flags	Card.	Type
Patient	N		DomainResource
identifier	Σ	0..*	Identifier
active	?! Σ	0..1	boolean
name	Σ	0..*	HumanName
telecom	Σ	0..*	ContactPoint
gender	Σ	0..1	code
birthDate	Σ	0..1	date
deceased[x]	?! Σ	0..1	
deceasedBoolean			boolean
deceasedDateTime			dateTime
address	Σ	0..*	Address
maritalStatus		0..1	CodeableConcept
multipleBirth[x]		0..1	
multipleBirthBoolean			boolean
multipleBirthInteger			integer
photo		0..*	Attachment
contact	I	0..*	BackboneElement
relationship		0..*	CodeableConcept
name		0..1	HumanName
telecom		0..*	ContactPoint
address		0..1	Address
gender		0..1	code
organization	I	0..1	Reference(Organization)
period		0..1	Period
communication		0..*	BackboneElement
language		1..1	CodeableConcept
preferred		0..1	boolean
generalPractitioner		0..*	Reference(Organization | Practitioner | PractitionerRole)
managingOrganization	Σ	0..1	Reference(Organization)
link	?! Σ	0..*	BackboneElement
other	Σ	1..1	Reference(Patient | RelatedPerson)
type	Σ	1..1	code

SEQ	LEN	DT	OPT	RP/#	ELEMENT NAME
1	4	SI	O		Set ID - PID
2	20	CX	B		Patient ID
3	250	CX	R	Y	Patient Identifier List
4	20	CX	B	Y	Alternate Patient ID -
5	250	XPN	R	Y	Patient Name
6	250	XPN	O	Y	Mother's Maiden Nam
7	26	TS	O		Date/Time of Birth
8	1	IS	O		Administrative Sex
9	250	XPN	B	Y	Patient Alias
10	250	CE	O	Y	Race
11	250	XAD	O	Y	Patient Address
12	4	IS	B		County Code
13	250	XTN	O	Y	Phone Number - Home
14	250	XTN	O	Y	Phone Number - Business
15	250	CE	O		Primary Language
16	250	CE	O		Marital Status
17	250	CE	O		Religion
18	250	CX	O		Patient Account Number
19	16	ST	B		SSN Number - Patient
20	25	DLN	B		Driver's License Number - Patient
21	250	CX	O	Y	Mother's Identifier
22	250	CE	O	Y	Ethnic Group
23	250	ST	O		Birth Place
24	1	ID	O		Multiple Birth Indicator
25	2	NM	O		Birth Order
26	250	CE	O	Y	Citizenship
27	250	CE	O		Veterans Military Status
28	250	CE	B		Nationality
29	26	TS	O		Patient Death Date and Time
30	1	ID	O		Patient Death Indicator
31	1	ID	O		Identity Unknown Indicator
32	20	IS	O	Y	Identity Reliability Code
33	26	TS	O		Last Update Date/Time
34	241	HD	O		Last Update Facility
35	250	CE	C		Species Code
36	250	CE	C		Breed Code
37	80	ST	O		Strain
38	250	CE	O	2	Production Class Code
39	250	CWE	O	Y	Tribal Citizenship

Value	Description
F	Female
M	Male
O	Other
U	Unknown
A	Ambiguous
N	Not applicable

Patient ←→PID

Name	Flags	Card.	Type
Patient	N		DomainResource
identifier	Σ	0..*	Identifier
active	?! Σ	0..1	boolean
name	Σ	0..*	HumanName
telecom	Σ	0..*	ContactPoint
gender	Σ	0..1	code
birthDate	Σ	0..1	date
deceased[x]	?! Σ	0..1	
deceasedBoolean			boolean
deceasedDateTime			dateTime
address	Σ	0..*	Address
maritalStatus		0..1	CodeableConcept
multipleBirth[x]		0..1	
multipleBirthBoolean			boolean
multipleBirthInteger			integer
photo		0..*	Attachment
contact	I	0..*	BackboneElement
relationship		0..*	CodeableConcept
name		0..1	HumanName
telecom		0..*	ContactPoint
address		0..1	Address
gender		0..1	code
organization	I	0..1	Reference(Organization)
period		0..1	Period
communication		0..*	BackboneElement
language		1..1	CodeableConcept
preferred		0..1	boolean
generalPractitioner		0..*	Reference(Organization | Practitioner | PractitionerRole)
managingOrganization	Σ	0..1	Reference(Organization)
link	?! Σ	0..*	BackboneElement
other	Σ	1..1	Reference(Patient | RelatedPerson)
type	Σ	1..1	code

SEQ	LEN	DT	OPT	RP/#	ELEMENT NAME
1	4	SI	O		Set ID - PID
2	20	CX	B		Patient ID
3	250	CX	R	Y	Patient Identifier List
4	20	CX	B	Y	Alternate Patient ID - PID
5	250	XPN	R	Y	Patient Name
6	250	XPN	O	Y	Mother's Maiden Name
7	26	TS	O		Date/Time of Birth
8	1	IS	O		Administrative Sex
9	250	XPN	B	Y	Patient Alias
10	250	CE	O	Y	Race
11	250	XAD	O	Y	Patient Address
12	4	IS	B		County Code
13	250	XTN	O	Y	Phone Number - Home
14	250	XTN	O	Y	Phone Number - Business
15	250	CE	O		Primary Language
16	250	CE	O		Marital Status
17	250	CE	O		Religion
18	250	CX	O		Patient Account Number
19	16	ST	B		SSN Number - Patient
20	25	DLN	B		Driver's License Number - Patient
21	250	CX	O	Y	Mother's Identifier
22	250	CE	O	Y	Ethnic Group
23	250	ST	O		Birth Place
24	1	ID	O		Multiple Birth Indicator
25	2	NM	O		Birth Order
26	250	CE	O	Y	Citizenship
27	250	CE	O		Veterans Military Status
28	250	CE	B		Nationality
29	26	TS	O		Patient Death Date and Time
30	1	ID	O		Patient Death Indicator
31	1	ID	O		Identity Unknown Indicator
32	20	IS	O	Y	Identity Reliability Code
33	26	TS	O		Last Update Date/Time
34	241	HD	O		Last Update Facility
35	250	CE	C		Species Code
36	250	CE	C		Breed Code
37	80	ST	O		Strain
38	250	CE	O	2	Production Class Code
39	250	CWE	O	Y	Tribal Citizenship

【例】Gender Codeの比較

Name	Flags	Card.	Type
Patient	N		DomainResource
identifier	Σ	0..*	Identifier
active	?! Σ	0..1	boolean
name	Σ	0..*	HumanName
telecom	Σ	0..*	ContactPoint
gender	Σ	0..1	code
birthDate	Σ	0..1	date
deceased[x]	?! Σ	0..1	
deceasedBoolean			boolean
deceasedDateTime			dateTime
address	Σ	0..*	Address
maritalStatus		0..1	CodeableConcept
multipleBirth[x]		0..1	
multipleBirthBoolean			boolean
multipleBirthInteger			integer
photo		0..*	Attachment
contact	I	0..*	BackboneElement
relationship		0..*	CodeableConcept
name		0..1	HumanName
telecom		0..*	ContactPoint
address		0..1	Address
gender		0..1	code
organization	I	0..1	Reference(Organization)
period		0..1	Period
communication		0..*	BackboneElement
language		1..1	CodeableConcept
preferred		0..1	boolean
generalPractitioner		0..*	Reference(Organization | Practitioner | PractitionerRole)
managingOrganization	Σ	0..1	Reference(Organization)
link	?! Σ	0..*	BackboneElement
other	Σ	1..1	Reference(Patient | RelatedPerson)
type	Σ	1..1	code

FHIR

Code	Display	Definition
male	Male	Male.
female	Female	Female.
other	Other	Other.
unknown	Unknown	Unknown.

V2

Value	Description
F	Female
M	Male
O	Other
U	Unknown
A	Ambiguous
N	Not applicable

V3

Code	Concept ID	Print Name	Definition/Description
F	10174	Female	Female
M	10173	Male	Male
UN	17718	Undifferentiated	The gender of a person could not be uniquely defined as male or female, such as hermaphrodite
CWE	*coded with extensions, meaning that the code set can be expanded to meet local implementation needs*		

Human Name[FHIR←→V2]

Name	Flags	Card.	Type	Description & Constraints
HumanName	Σ N		Element	Name of a human - parts and usage Elements defined in Ancestors: id, extension
use	?! Σ	0..1	code	usual | official | temp | nickname | anonymous | old | maiden
text	Σ	0..1	string	
family	Σ	0..1	string	
given	Σ	0..*	string	
prefix	Σ	0..*	string	
suffix	Σ	0..*	string	
period	Σ	0..1	Period	

SEQ	LEN	DT	OPT	COMPONENT NAME
1	194	FN	O	Family Name
2	30	ST	O	Given Name
3	30			
4	20			
5	20			
6	6			
7	1			
8	1			
9	48			
10	53			
11	1			
12	26			
13	26			
14	199	ST	O	Professional Suffix

Value	Description
A	Alias Name
B	Name at Birth
C	Adopted Name
D	Display Name
I	Licensing Name
L	Legal Name
M	Maiden Name
N	Nickname /"Call me" Name/Street Name
P	Name of Partner/Spouse (retained for backward compatibility only)
R	Registered Name (animals only)
S	Coded Pseudo-Name to ensure anonymity
T	Indigenous/Tribal/Community Name
U	Unspecified

Human Name extension (80%ルール)

```
<name>
  <extension url="http://hl7.org/fhir/StructureDefinition/iso21090-EN-representation">
      <valueCode value="IDE" />
  </extension>
  <family value="東京" />
  <given value="太郎" />
  </name>
<name>
  <extension url="http://hl7.org/fhir/StructureDefinition/iso21090-EN-representation">
      <valueCode value="SYL" />
  </extension>
 <family value="とうきょう" />
 <given value="たろう" />
</name>
<name>
  <extension url="http://hl7.org/fhir/StructureDefinition/iso21090-EN-representation">
      <valueCode value="ABC" />
  </extension>
  <family value="Tokyo" />
  <given value="Tarou" />
</name>
```

統合開発環境支援:Eclipse

```
package ca.uhn.fhir.example;

import org.hl7.fhir.dstu3.model.HumanName;
import org.hl7.fhir.dstu3.model.Identifier;
import org.hl7.fhir.dstu3.model.Patient;

public class Example01_CreateAPatient {
  public static void main(String[] theArgs) {
    // Create a resource instance
    Patient pat = new Patient();
    // Add a "name" element
    HumanName name = pat.addName(
    name.setFamily("Simpson").addGive
    // Add an "identifier" element
    Identifier identifier = pat.addIdentifi
    identifier.setSystem("http://acme.or
    // Model is designed to be chained
    pat.addIdentifier().setSystem("http:/
  }
}
```



```
<?xml version="1.0" encoding="UTF-8"?>
<Patient xmlns="http://hl7.org/fhir">
  <id value="glossy"/>
  <meta>
    <lastUpdated value="2014-11-13T11:41:00+11:00"/>
  </meta>
  <text>
    <status value="generated"/>
    <div xmlns="http://www.w3.org/1999/xhtml">
      <p> Henry Levin the 7th</p>
      <p> MRN: 123456. Male, 24-Sept 1932</p>
    </div>
  </text>
  <extension url="http://example.org/StructureDefinition/trials">
    <valueCode value="renal"/>
  </extension>
  <identifier>
    <use value="usual"/>
    <type>
      <coding>
        <system value="http://terminology.hl7.org/CodeSystem/v2-0203"/>
        <code value="MR"/>
      </coding>
    </type>
    <system value="http://www.goodhealth.org/identifiers/mrn"/>
    <value value="123456"/>
  </identifier>
  <active value="true"/>
  <name>
    <family value="Levin"/>
    <given value="Henry"/>
    <suffix value="The 7th"/>
  </name>
  <gender value="male"/>
  <birthDate value="1932-09-24"/>
  <generalPractitioner>
    <reference value="Practitioner/example"/>
    <display value="Dr Adam Careful"/>
  </generalPractitioner>
  <managingOrganization>
    <reference value="Organization/2"/>
    <display value="Good Health Clinic"/>
  </managingOrganization>
</Patient>
```

Resource, Identity, Metadata

Human Readable Summary
安全確保のための Fallback

Extension with reference(URL) to definition

Standard Data

- MR(V2 0203 Medical Record Number)
- Name
- Gender
- Date of Birth
- Provider

SS-MIX(旧)(HL7 V2) → FHIR変換

MSH|^~¥&|DOCX|HIS|GW|GW|20060424190111710||OML^O33^OML_O33|20060424000001|P|2.5||||~ISO IR87||ISO 2022-1994
ZGW|1014360|20050401000000|OML-01^検体検査オーダ^L|000000003005077|UPD|002^内科^L
PID|0001||1014360||駿河^葵^^^^^L^I~スルガ^アオイ^^^^^L^P||19520717|F
PV1|0001|O|002^^^^^C||||298^医師298^^^^^^^^L|||002
ZIN|1^政府管掌健康保険^HL7-0072
SPM|0001|||015^便^JC10^40^便^L
ORC|NW|000000003005077|||||||20050401000000|298^医師298^^^^^^^^L||298^医師298^^^^^^^^L|002^^^^^C||||002^内科^L|Fu^^L|||登呂病院|^静岡市駿河区登呂3-1-1^^^422-8033^jpn|054-284-9122||||||O^外来患者^HL7-0482
OBR|0001|000000003005077|000000003005077|4^一般^L||20030401160212|20030401|20030401|||||||015&便&JC10&40&便&L|298^医師298^^^^^^^^L||||||20030401172022
OBX|0001|ST|^便潜血^JC10^44100^便潜血^L||||(-)|||||||20050401000000
OBX|0002|ST|1B035000001590111^ オルトトリジン^JC10^44101^ オルトトリジン^L||(2+)|||||||||20050401000000
OBX|0003|ST|1B030000001590111^ グアヤック脂^JC10^44102^ グアヤック脂^L||(+-)|||||||||20050401000000
OBX|0004|ST|1B040000001502311^ヒトヘモグロビン^JC10^44103^ヒトヘモグロビン^L||(+)||(-)|||||||20050401000000
OBX|0005|ST|^クロストリジウムトキシンA^JC10^44129^クロストリジウムトキシンA^L||(+)||(-)|||||||20050401000000

試行過程

- Main.java
- Ex01CreatePatient.java
- Ex02CreateObservation.java
- Ex03CreateBudle.java

- ReadMessage.java
- CreatePatient.java
- CreateObservation.java
- V2_Patient.java
- V2toFHIR.java

- MSH.java
- PID.java
- SPM.java
- OBR.java
- ORC.java
- OBX.java
- CE.java
- CQ.java
- CWE.java
- DR.java
- EI.java
- EIP.java
- HD.java
- PL.java
- PV1.java
- SPS.java
- XCN.java
- XPN.java
- XTN.java



```
package hl7.v2;

import org.hl7.fhir.dstu3.model.Patient;

import ca.uhn.fhir.context.FhirContext;
import ca.uhn.fhir.parser.IParser;

public class Ex01CreatePatient {

public static void main(String[] args) {
ReadMessage rd = new ReadMessage();
rd.readV2Message(args[0]); // read V2 message
/**
* FHIRPatientリソース生成
*/
Patient pat = (new CreatePatient()).cPatient(rd);
// FHIRコンテクストに変換
FhirContext ctx = FhirContext.forDstu3();
// IParser parser = ctx.newJsonParser(); // Json変換
IParser parser = ctx.newXmlParser(); // XML変換


parser.setPrettyPrint(true);
String encode = parser.encodeResourceToString(pat);
System.out.println(encode);
```

Patientリソースの出力

V2 message を FHIR リソース(XML)

MSH|^~¥&|DOCX|HIS|GW|GW|20060424190111710||OML^O33^OML_O33|20060424000001|P|2.5||||||~ISO IR87||ISO 2022-1994
.
.
PID|0001||1014360||駿河^葵^^^^^L^I~スルガ゛^アオイ^^^^^L^P||19520717|F

```
<Patient xmlns="http://hl7.org/fhir">
  <identifier>
    <system value="http://www.hl7.jp"></system>
    <value value="1014360"></value>
  </identifier>
  <name>
    <extension url="http://hl7.org/fhir/StructureDefinition/iso21090-EN-representation">
      <valueCode value="IDE"></valueCode>
    </extension>
    <family value="駿河"></family>
    <given value="葵"></given>
  </name>
  <name>
    <extension url="http://hl7.org/fhir/StructureDefinition/iso21090-EN-representation">
      <valueCode value="SYL"></valueCode>
    </extension>
    <family value="スルガ゛"></family>
    <given value="アオイ"></given>
  </name>
  <gender value="female"></gender>
  <birthDate value="1952-07-17"></birthDate>
</Patient>
```

PatientリソースをHAPI-FHIRサーバにCreate

POST

PatientリソースID

バージョン番号

付加された情報

```
<Patient xmlns="http://hl7.org/fhir">
  <id value="1977167"/>
  <meta>
    <versionId value="1"/>
    <lastUpdated value="2019-07-08T03:53:56.065+00:00"/>
  </meta>
  <text>
    <status value="generated"/>
    <div xmlns="http://www.w3.org/1999/xhtml">
      <div class="hapiHeaderText">葵

        <b>駿河 </b>
      </div>
      <table class="hapiPropertyTable">
        <tbody>
          <tr>
            <td>Identifier</td>
            <td>1014360</td>
          </tr>
          <tr>
            <td>Date of birth</td>
            <td>
              <span>17 July 1952</span>
            </td>
          </tr>
        </tbody>
      </table>
    </div>
  </text>
  <identifier>
    <system value="http://www.hl7.jp"/>
    <value value="1014360"/>
  </identifier>
  <name>
    <extension
url="http://hl7.org/fhir/StructureDefinition/iso21090-EN-representation">
      <valueCode value="IDE"/>
    </extension>
    <family value="駿河"/>
    <given value="葵"/>
  </name>
  <name>
    <extension
url="http://hl7.org/fhir/StructureDefinition/iso21090-EN-representation">
      <valueCode value="SYL"/>
    </extension>
    <family value="スルガ゛"/>
    <given value="アオイ"/>
  </name>
  <gender value="female"/>
  <birthDate value="1952-07-17"/>
</Patient>
```

HAPI FHIR サーバからPatient リソースRead

(http://hapi.fhir.org/baseDstu3/Patient/1977167)

```
<Patient xmlns="http://hl7.org/fhir">
  <id value="1977167"/>
  <meta>
    <versionId value="1"/>
    <lastUpdated value="2019-07-08T00:52:56.065+00:00"/>
  </meta>
  <text>
    <status value="generated"/>
    <div xmlns="http://www.w3.org/1999/xhtml">
      <div class="hapiHeaderText">葵

        <b>駿河 </b>
      </div>
      <table class="hapiPropertyTable">
        <tbody>
          <tr>
            <td>Identifier</td>
            <td>1014360</td>
          </tr>
          <tr>
            <td>Date of birth</td>
            <td>
              <span>17 July 1952</span>
            </td>
          </tr>
        </tbody>
      </table>
    </div>
  </text>
  <identifier>
    <system value="http://www.hl7.jp"/>
    <value value="1014360"/>
  </identifier>
  <name>
    <extension
url="http://hl7.org/fhir/StructureDefinition/iso21090-EN-
representation">
      <valueCode value="IDE"/>
    </extension>
    <family value="駿河"/>
    <given value="葵"/>
  </name>
  <name>
    <extension
url="http://hl7.org/fhir/StructureDefinition/iso21090-EN-
representation">
      <valueCode value="SYL"/>
    </extension>
    <family value="スルガ゛"/>
    <given value="アオイ"/>
  </name>
  <gender value="female"/>
  <birthDate value="1952-07-17"/>
</Patient>
```

Patientの誕生日を変更
UPDATE(PUT)

```
<Patient xmlns="http://hl7.org/fhir">
  <id value="1977167"/>
  <identifier>
    <system value="http://www.hl7.jp"></system>
    <value value="1014360"></value>
  </identifier>
  <name>
    <extension url="http://hl7.org/fhir/StructureDefinition/iso21090-EN-representation">
      <valueCode value="IDE"></valueCode>
    </extension>
    <family value="駿河"></family>
    <given value="葵"></given>
  </name>
  <name>
    <extension url="http://hl7.org/fhir/StructureDefinition/iso21090-EN-representation">
      <valueCode value="SYL"></valueCode>
    </extension>
    <family value="スルガ゛"></family>
    <given value="アオイ"></given>
  </name>
  <gender value="female"></gender>
  <birthDate value="1950-07-17"></birthDate>
</Patient>
```

PatientリソースID

誕生日

http://hapi.fhir.org/baseDstu3/Patient/1977167/_history

```
<Bundle xmlns="http://hl7.org/fhir">
  <id value="9724b630-eb15-4927-88cc-862a9bf4d28d"/>
  <meta>
    <lastUpdated value="2019-07-08T04:23:05.681+00:00"/>
  </meta>
  <type value="history"/>
  <total value="2"/>
  <link>
    <relation value="self"/>
    <url
value="http://hapi.fhir.org/baseDstu3/Patient/1977167/_history"/>
  </link>
  <entry>
    <fullUrl
value="http://hapi.fhir.org/baseDstu3/Patient/1977167"/>
    <resource>
      <Patient xmlns="http://hl7.org/fhir">
        <id value="1977167"/>
        <meta>
          <versionId value="2"/>
          <lastUpdated value="2019-07-
08T01:57:00.764+00:00"/>
        </meta>
        <text>
          <status value="generated"/>
.
.
                    </tr>
                    <tr>
                      <td>Date of birth</td>
                      <td>
                        <span>17 July 1950</span>
.
.
  </entry>
  <entry>
    <fullUrl
value="http://hapi.fhir.org/baseDstu3/Patient/1977167"/>
    <resource>
      <Patient xmlns="http://hl7.org/fhir">
        <id value="1977167"/>
        <meta>
          <versionId value="1"/>
          <lastUpdated value="2019-07-
08T00:52:56.065+00:00"/>
        </meta>
        <text>
          <status value="generated"/>
          <div xmlns="http://www.w3.org/1999/xhtml">
            <div class="hapiHeaderText">葵

              <b>駿河 </b>
            </div>
            <table class="hapiPropertyTable">
.
.
                    <span>17 July 1952</span>
                  </td>
.
.
    <request>
      <method value="POST"/>
      <url
value="http://hapi.fhir.org/baseDstu3/Patient/1977167/_history/1"/>
    </request>
  </entry>
</Bundle>
```

http://hapi.fhir.org/baseDstu3/Patient?name=駿河

```
<Bundle xmlns="http://hl7.org/fhir">
  <id value="cd30933d-16ff-420c-a759-8e7b02be5393"/>
  <meta>
    <lastUpdated value="2019-07-08T07:58:25.629+00:00"/>
  </meta>
  <type value="searchset"/>
  <total value="4"/>
  <link>
    <relation value="self"/>
    <url
value="http://hapi.fhir.org/baseDstu3/Patient?identifier=1014360"/>
  </link>
  <entry>
    <fullUrl
value="http://hapi.fhir.org/baseDstu3/Patient/1947172"/>
    <resource>
      <Patient xmlns="http://hl7.org/fhir">
        <id value="1947172"/>
        <meta>
          <versionId value="1"/>
            .
            .
        <identifier>
          <system value="http://www.hl7.jp"/>
          <value value="1014360"/>
            .
      <resource>
        <Patient xmlns="http://hl7.org/fhir">
          <id value="1950052"/>
          <meta>
            <versionId value="1"/>
              .
          <identifier>
            <system value="http://www.hl7.jp"/>
            <value value="1014360"/>
          </identifier>
        <Patient xmlns="http://hl7.org/fhir">
          <id value="1951763"/>
          <meta>
            <versionId value="1"/>
              .
          <identifier>
            <system value="http://www.hl7.jp"/>
            <value value="1014360"/>
          </identifier>
            .
        <Patient xmlns="http://hl7.org/fhir">
          <id value="1977167"/>
          <meta>
            <versionId value="2"/>
              .
          <identifier>
            <system value="http://www.hl7.jp"/>
            <value value="1014360"/>
          </identifier>
          <name>
            <extension
url="http://hl7.org/fhir/StructureDefinition/iso21090-EN-
representation">
              <valueCode value="IDE"/>
            </extension>
            <family value="駿河"/>
              .
          </name>
          <gender value="female"/>
          <birthDate value="1950-07-17"/>
        </Patient>
      </resource>
      <search>
        <mode value="match"/>
      </search>
    </entry>
</Bundle>
```

Observation リソース
OBX←→Observation



OBR

SEQ	LEN	DT	OPT	RP/#	TBL#	ITEM #	ELEMENT NAME
1	4	SI	O			237	Set ID - OBR
2	22	EI	C			216	Placer Order Number
3	22	EI	C			217	Filler Order Number
4	250	CE	R			238	Universal Service Identifier
5	2	ID	X			239	Priority – OBR
6	26	TS	X			240	Requested Date/Time

SEQ	LEN	DT	OPT	RP/#	TBL#	ITEM#	ELEMENT NAME
1	4	SI	O			569	Set ID – OBX
2	2	ID	C		125	570	Value Type
3	250	CE	R			571	Observation Identifier
4	20	ST	C			572	Observation Sub-ID
5	99999[1]	varies	C	Y[2]		573	Observation Value
6	250	CE	O			574	Units
7	60	ST	O			575	References Range
8	5	IS	O	Y	78	576	Abnormal Flags
9	5	NM	O			577	Probability
10	2	ID	O	Y	80	578	Nature of Abnormal Test
11	1	ID	R		85	579	Observation Result Status
12	26	TS	O			580	Effective Date of Reference Range
13	20	ST	O			581	User Defined Access Checks
14	26	TS	O			582	Date/Time of the Observation
15	250	CE	O			583	Producer's ID
16	250	XCN	O	Y		584	Responsible Observer
17	250	CE	O	Y		936	Observation Method
18	22	EI	O	Y		1479	Equipment Instance Identifier
19	26	TS	O			1480	Date/Time of the Analysis

OBX→Observation

OBX|0004|NM|1A030000000390301^比重^JC10^40003^比重^L||1.020||1.005～1.030|||||20050402000000

```
Observation obs = new Observation();
obs.setStatus(ObservationStatus.FINAL);
OBX ox = rd.obx[obxInd];
if (ox.date != null)
        obs.setEffective(new DateTimeType((new V2toFHIR()).dateTime(ox.date)));
Identifier id = obs.addIdentifier();
id.setSystem(organization).setValue(rd.obr.svID.ID);
obs.getSubject().setDisplay("駿河 葵").setReference("Patient/1977167");
CodeableConcept cd = new CodeableConcept();
cd.addCoding().setSystem(ox.obsId.uri)
        .setCode(ox.obsId.ID)
        .setDisplay(ox.obsId.Tx);
obs.setCode(cd);
obs.addReferenceRange().setText(ox.reRg);

if (ox.type.equals("ST")) {
        StringType value = new StringType(ox.value);
        obs.setValue(value);
}
else {
    Quantity value = new Quantity();
    value.setValue(Float.parseFloat(ox.value)).setSystem(ox.obsId.uri).setCode(ox.unit);
    obs.setValue(value);
}
```

Patient リソースから

Observationリソースの作成とCreate(POST)

```
        Observation obs = (new CreateObservation()).CreateObservation(rd, 4);

        FhirContext ctx = FhirContext.forDstu3();
//      IParser parser = ctx.newJsonParser();       // Json変換
        IParser parser = ctx.newXmlParser();        // XML変換
        parser.setPrettyPrint(true);                // 清書

        String encode = parser.encodeResourceToString(obs);
        System.out.println(encode);
```

```
        String serverBaseUrl = "http://hapi.fhir.org/baseDstu3";

        IGenericClient client = ctx.newRestfulGenericClient(serverBaseUrl);

//      Observation リソースのCreate
        MethodOutcome outcome = client
                .create()
                .resource(obs)
                .execute();
//      リソースIDの取得
        System.out.println(outcome.getId());
```

Create Observation Resource

POST http://hapi.fhir.org/baseDstu3/Observation

```
<Observation xmlns="http://hl7.org/fhir">
  <identifier>
    <system
value="http://www.hl7.jp"></system>
    <value value="4"></value>
  </identifier>
  <status value="final"></status>
  <code>
    <coding>
      <system
value="http://www.jslm.org"></system>
      <code
value="1A035000000390101"></code>
      <display value="PH"></display>
    </coding>
  </code>
  <subject>
    <reference
value="Patient/1977167"></reference>
    <display value="駿河 葵"></display>
  </subject>
  <effectiveDateTime value="2005-04-
02T00:00:00+09:00"></effectiveDateTime>
  <valueQuantity>
    <value value="6.0"></value>
    <system
value="http://www.jslm.org"></system>
  </valueQuantity>
  <referenceRange>
    <text value="5.0～7.5（平均6.0）"></text>
  </referenceRange>
</Observation>
```

Read Observation resource/1982273

GET http://hapi.fhir.org/baseDstu3/Observation/1982273

```
<Observation xmlns="http://hl7.org/fhir">
  <id value="1982273"/>
  <meta>
    <versionId value="1"/>
    <lastUpdated value="2019-07-13T05:40:19.425+00:00"/>
  </meta>
  <identifier>
    <system value="http://www.hl7.jp"/>
    <value value="4"/>
  </identifier>
  <status value="final"/>
  <code>
    <coding>
      <system value="http://www.jslm.org"/>
      <code value="1A035000000390101"/>
      <display value="PH"/>
    </coding>
  </code>
  <subject>
    <reference value="Patient/1977167"/>
    <display value="駿河 葵"/>
  </subject>
  <effectiveDateTime value="2005-04-02T00:00:00+09:00"/>
  <valueQuantity>
    <value value="6.0"/>
    <system value="http://www.jslm.org"/>
  </valueQuantity>
  <referenceRange>
    <text value="5.0～7.5（平均6.0）"/>
  </referenceRange>
</Observation>
```

検査結果
Resource DiagnosticReport

CBC Report for Wile. E. COYOTE (MRN: 23453) issued 3-Mar 2011 11:45

Test	Units	Value	Reference Range
Haemoglobin	g/L	176	135 - 180
Red Cell Count	x10*12/L	5.9	4.2 - 6.0
Haematocrit		0.55+	0.38 - 0.52
Mean Cell Volume	fL	99+	80 - 98
Mean Cell Haemoglobin	pg	36+	27 - 35
Platelet Count	x10*9/L	444	150 - 450
White Cell Count	x10*9/L	4.6	4.0 - 11.0
Neutrophils	%	20	
Neutrophils	x10*9/L	0.9---	2.0 - 7.5
Lymphocytes	%	20	
Lymphocytes	x10*9/L	0.9-	1.1 - 4.0
Monocytes	%	20	
Monocytes	x10*9/L	0.9	0.2 - 1.0
Eosinophils	%	20	
Eosinophils	x10*9/L	0.92++	0.04 - 0.40
Basophils	%	20	
Basophils	x10*9/L	0.92+++	<0.21

リソース (Json)　30ページ



ご静聴ありがとうございました